

# CL-EPOXY FLOOR



## Cleaner for epoxy floorings

### Description

Special liquid cleaner for epoxy floorings. CL-EPOXY FLOOR cleans deeply the epoxy floorings without affecting their shining.

### Fields of application

CL-EPOXY FLOOR is used to clean stains of oils, grease and other intense stains from epoxy floorings. It is ideal for any area with an epoxy flooring such as industries, parking lots etc. It is also suitable for cleaning stains of grease and oils on areas such as kitchens, restaurants etc.

### Technical data

Form : liquid  
pH : 10,4-11,4

### Directions for use

CL-EPOXY FLOOR is applied undiluted on the surface to be cleaned and is left to dilute the stain for a few minutes, then the surface is brushed by a broom or a sponge and finally it is rinsed with plenty of water. For floor mopping it is diluted in a ratio of 50ml : 3l of water.

### Consumption

15-20m<sup>2</sup>/l ,depending on kind of stains.

### Packaging

Supplied on containers of 0,75l, 5l and 20l.

### Storage

12 months from production date if stored in original, unopened packaging, in temperature between +5°C and +35°C. Protect from direct sun exposure and frost.

### Remarks

- Consult the usage risks and safety advice written on the container.
- Risk of serious damage to eyes. Keep out of the reach of children. If swallowed, seek medical advice immediately and show this container or label. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear eye/face protection.
- Contains more than 15% but less than 30% bleaching agent based on oxygen Also contains methylchloroisothiazolinone, methylisothiazolinone and perfume.

### ISOMAT S.A.

BUILDING CHEMICALS AND MORTARS

#### MAIN OFFICES - FACTORY:

17th km Thessaloniki - Ag. Athanasios Road,  
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,  
Tel.: +30 2310 576 000, Fax: +30 2310 722 475

[www.isomat.net](http://www.isomat.net) e-mail: [info@isomat.net](mailto:info@isomat.net)