Technical leaflet

CL-MOLD

isomat building quality

Special antimold agent

Description

Special liquid with antifungal activity for both indoor and outdoor use. Cleans and disinfects surfaces from mold, bacteria and algae. It is odorless and friendly for the user and the environment.

Fields of application

It can be applied to painted surfaces affected by mold, but also proactively to prevent the growth of microorganisms on the surface of the paint, in areas with high humidity. It is very effective in surfaces such as walls, ceilings, natural stones, bricks, cement, swimming pools, etc. Furthermore, it can be used for decontamination of fungi and for maintaining the sanitary conditions in areas such as kitchens, restaurants, hotels, industries or food warehouses, bakeries, etc.

Technical data

Form: liquid

Color: light blue

Density: 1 kg/l

pH: 6-7

Directions for use

As a liquid for removing mold: CL-MOLD is applied undiluted to the surface affected by mold, bacteria or algae, with a cloth or sponge and is left to act for at least 24 hours. Then remove the mold residue with a sponge, rinse with clean water and allow to completely dry.

Preventive use: Apply CL-MOLD onto the painted surfaces from time to time to ensure long term protection from the growth of microorganisms.

Disinfectant use: As a disinfectant liquid CL-MOLD is applied to surfaces diluted 1:10 with water.

Consumption

About 15-20 m² per litre, according to the surface absorption.

Packaging

Supplied on containers of 11.

Storage

12 months from production date if stored in original, unopened packaging, in temperature between +5°C and +35°C. Protect from direct sun exposure and frost.

Remarks

Consult the usage risks and safety advice written on the container.

ISOMAT S.A.

BUILDING CHEMICALS AND MORTARS MAIN OFFICES - FACTORY:

17th km Thessaloniki - Ag. Athanasios Road, P.O. BOX 1043, 570 03 Ag. Athanasios, Greece, Tel.: +30 2310 576 000, Fax: +30 2310 722 475

www.isomat.net e-mail: info@isomat.net

