

VS-1

Acrylic stone varnish

Description

VS-1 is a ready-to-use, transparent acrylic varnish with solvents, used to impregnate natural stones (slate or tufa stone etc.) and artificial building materials (decorative bricks, roof tiles, etc.).

- It provides great water-repellency.
- It offers durable protection.
- It brightens up the natural color of the material on which it is applied.
- It protects the surfaces from salt stains as well as frost and dirt, due to its resistance to rainwater and impurity absorption.
- It is suitable for indoor and outdoor use.

Fields of application

VS-1 brings out the natural color of the material on which it is applied, protecting at the same time the surfaces from rainwater and atmospheric pollution. It is suitable for the impregnation of natural stones, exposed masonry, roof tiles, etc. It is applied on walls and floors, both indoors and outdoors.

Technical data

Color: transparent
Density: 0.90 kg/l

Directions for use

1. Substrate preparation

The surfaces to be treated with VS-1 should have open pores. Adjacent surfaces such as windows, painted surfaces and materials susceptible to solvents, such as polystyrene, joint sealants, bitumen, etc., have to be protected during VS-1 application.

2. Application

The application of VS-1 is carried out by brush, roller or spraying in two layers. The second layer can be applied as soon as the first one has dried.

Consumption

150-200 ml/m² per layer, depending on the absorbency of the surface.

Packaging

VS-1 is supplied in metal containers of 1 l, 4 l and 10 l.

Shelf life – Storage

24 months from production date if stored in original, unopened packaging, at temperatures between +5°C and +35°C. Protect from direct sunlight and frost.

Volatile Organic Compounds (VOCs)

According to Directive 2004/42/CE (Annex II, table A), the maximum allowed VOC content for the product subcategory h, type SB is 750 g/l (2010) for the ready-to-use product. The ready-to-use product VS-1 contains a maximum of 750 g/l VOC.

ISOMAT S.A.
BUILDING CHEMICALS AND MORTARS
MAIN OFFICES - FACTORY:
17th km Thessaloniki - Ag. Athanasios Road,
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,
Tel.: +30 2310 576 000, Fax: +30 2310 722 475
www.isomat.eu e-mail: info@isomat.eu